



Technical Support

If you need technical support with your SSL product or have questions about its use, please contact us:

805.751.4855



Congratulations on your purchase of this Sound Storm Laboratories (SSL) SS Series Subwoofer. SSL takes great pride in producing products that look great, sound great, and stand up to the daily rigors applied by audio enthusiasts around the world. We appreciate your confidence and support and we thank you for choosing SSL.



SS8 10" (20 cm) Subwoofer

- *Single 4 Ω Voice Coil*
- *400 W Peak Power Handling*
- *1.2"(30mm) High Temperature Voice Coil*
- *Foam Surround*

Product Specifications

Impedance	4 Ω
Fs	59.2 Hz
Qts	0.786
Qms	5.334
Qes	0.922
Vas	0.564 cu ft. (15.97 liters)
Xmax	8 mm
Sensitivity (1 W/ 1 m)	87 dB
Peak Power Handling	400 W
Mounting Depth	3-7/16" (88mm)
Cutout Diameter	7-1/4" (184 mm)

Enclosure

A sealed enclosure is recommended. Below you will find the dimensions to make the enclosure to suit the parameters, it has been designed for maximum output while retaining great sound quality. The dimensions have already accounted for the volume displacement of the subwoofer, and using 3/4" (19mm) MDF. All dimensions are external. It has an internal volume of 0.90cu ft. (25.48 liters)

Dimensions:

Length (L) : 12.5" (482.6 mm)
 Width (W) : 12.5" (304.8 mm)
 Height (H) : 12.5" (355.6 mm)
 Cutout Diameter: 7-14" (184 mm)

